| Drive                                     | electric                   |
|---|----------------------------|
| Center of gravity of the load             | 600 kg                     |
| Equipped with a platform for the operator | NO                         |
| Lowering                                  | electrical                 |
| Lifting                                   | electrical                 |
| Maximum fork height                       | 1980 mm                    |
| Minimum fork height                       | 35mm                       |
| Fork length                               | 1070mm                     |
| Fork spacing                              | adjustable - max 610 mm    |
| Maximum travel speed with/without load    | 4.6 / 4.7 km/h             |
| lifting capacity                          | 1500 kg                    |
| Total length                              | 1520mm                     |
| Overall width                             | 1140mm                     |
| Drive wheel dimensions                    | 210x75mm                   |
| Brake type                                | electromagnetic            |
| Max lifting speed with/without load       | 75/110mm/sec               |
| Max lowering speed with/without load      | 145/100mm/sec              |
| Maximum lifting height                    | transport pallet - 1830 mm |
| Roller and wheel tread material           | polyurethane               |
| Libra                                     | 570 kg                     |
| Drive motor power                         | 2.2 kW                     |
| Front / Cargo wheel dimensions            | 100x60mm                   |
| Working time                              | 3 hours                    |
| Spacing between ramps                     | 957mm                      |
| The maximum height of the pallet truck    | 2800mm                     |
| The minimum height of the pallet truck    | 1520mm                     |
|   |                            |