

1	lifting capacity	kg	1200
2	Center of gravity of the load	mm	600
3	Equipped with a platform for the operator		NO
4	Drive		electric
5	Lowering		electrical
6	Lifting		electrical
7	Maximum lifting height	mm	3300
8	Minimum fork height	mm	80
9	Fork width	mm	170
10	Fork spacing	mm	570
11	Fork length	mm	1150
12	turning radius	mm	1408
13	Minimum working aisle width of the pallet 800x1200	mm	2150
14	Max travel speed with/without load	km/h	3.5/4.0
15	Max lifting speed with/without load	mm/sec	120/220
16	Max lowering speed with/without load	mm/sec	120/110
17	With the battery	kg	675
18	Total length	mm	1730
19	Overall width	mm	800
20	Maximum mast height	mm	3760
21	Minimum mast height	mm	2210
22	Wheel tread material		polyurethane
23	Arrangement of rollers and wheels		1x steering wheel 1x side 4 x front
24	Steering wheel dimensions	mm	210x70
25	Fork roller dimensions	mm	80x60
26	Dimensions of the side wheels	mm	130x55
27	Brake type		electromagnetic
28	drive	kW	0.65
29	lifting	kW	2.2
thirtv	Tension	V	12
31	Capacity	Ah	105
32	Technology		gel
33	Number of batteries installed	pcs.	2
34	Control system		DC
35	Speed adjustment potentiometer, CURTIS battery charge indicator, protective plexiglass, power disconnect		
36	All forklift trucks with a mechanical lifting drive are subject to technical supervision.		